



AKTUELT NYT

TUNE KABELNET

RADIO & TV

INTERNET

TELEFONI

TEKNIK

Kabler m.m.

Type	DVU 1-4	DVU 4	DVU 7
Item no.	41138	41134	41135
Version	Diplex	Standard	Standard
Data			
Frequency range forward (MHz)	118 - 1000	5 - 1000	5 - 1000
Frequency range reverse (MHz)	5 - 65	5 - 1000	5 - 1000
Insertion loss forward (dB)	4.0 (± 0.8)	3.5	7
Insertion loss reverse (dB)	0.6 (± 0.6)	3.5	7
Return loss	Cat. B*	Cat. B*	Cat. B*
Isolation Data-TV/R (5-65 MHz) (dB)	> 50	> 65	> 55
Isolation Data-TV/R (88-1000 MHz) (dB)	> 20	> 20	> 18
TV/R			
Frequency range (MHz)	87.5 - 1000	87.5 - 1000	87.5 - 1000
Insertion loss (88-1000 MHz) (dB)	4.0 (± 0.8)	3.5	2
Return loss	Cat. B*	Cat. B*	Cat. B*
General			
Input return loss (5-1000 MHz)	Cat. B*	Cat. B*	Cat. B*
Connectors	F-female	F-female	F-female
Screening effectiveness (5-30 MHz)	> 90 dB	> 90 dB	> 90 dB
Screening effectiveness (30-300 MHz)	> 85 dB	> 85 dB	> 85 dB
Screening effectiveness (300-470 MHz)	> 80 dB	> 80 dB	> 80 dB
Screening effectiveness (470-1000 MHz)	> 75 dB	> 75 dB	> 75 dB
Operating temperature °C	0 - 55	0 - 55	0 - 55
Dimensions (H x W x D mm)	19 x 66.5 x 50	19 x 66.5 x 50	19 x 66.5 x 50

* According to CENELEC EN50083-4; return loss Cat. B: 5-40 MHz ≥ 18 dB
40-1000 MHz ≥ 18 dB ÷ 1.5/oct.

Kilde: DKT - fabrikantens vejledning

Tune Kabelnet Hjemmeside | Kontakt os | Ris & Ros © 2000-2015 Tune Kabelnet. Med forbehold for skrivefejl. Alle rettigheder forbeholdt. Senest opdateret: